

OZGEN® OZONE GENERATORS

OXYGEN USAGE FOR OZGEN® OZONE GENERATORS

Ozone Generator Model	Ozone Output g/h O ₃	Oxygen Flow (100% Purity)			
		at 4% w/w O ₃		at 6% w/w O ₃	
		m ³ /hr	scfm	m ³ /hr	scfm
WT10C	20	0.377	0.222	0.252	0.148
WT20C	40	0.755	0.444	0.5	0.294
WT30C	60	1.132	0.666	0.755	0.444
WT40E/AR	80	1.51	0.888	1.0	0.588
WT60E/AR	120	2.265	1.333	1.51	0.888
WT100E/AR	200	3.775	2.222	2.52	1.483
WT200E/AR	400	7.55	4.44	5.0	2.94
WT300E	600	11.3	6.65	7.56	4.45
WT400E/AR	800	15.1	8.89	10.0	5.88
WT500AR	1000	18.87	11.1	12.6	7.42
WT600AR	1200	22.6		15.12	8.9
WT700AR	1400	26.4	15.53	17.6	10.35
WT800AR	1600	30.2	17.77	20.1	11.83
WT900AR	1800	34.0	20	22.7	13.36
WT1000AR	2000	37.75	22.2	25.2	14.83
WT1100AR	2200	41.5	24.4	27.7	16
WT1200AR	2400	45.3	26.66	30.2	17.77
WT1300AR	2600	49.0	28.8	32.76	19.28
WT1400AR	2800	52.85	31.1	35.3	20.77
WT1500AR	3000	56.6	33.3	37.8	22.25

Australia

Watertec Engineering Pty Ltd

20 Lochlarmey St,
Beenleigh, Brisbane, QLD,
Australia, 4207

Phone: +617 3287 1288

Fax: +617 3287 2800

Email: sales@watertecengineering.com

Web: www.watertecengineering.com

Malaysia

Waterotec (M) Sdn Bhd

Lot 5, Jalan Perusahaan 3/3, Batu 20,
48000 Rawang, Selangor,
Malaysia

Phone: +603 6092 9029

Fax: +603 6092 9025

Email: sales@waterotec.com

Web: www.watertecengineering.com



(A.B.N. 76 108 009 972)